




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F16D 69/04	A1	(11) International Publication Number: WO 00/49308 (43) International Publication Date: 24 August 2000 (24.08.00)
(21) International Application Number: PCT/CA00/00159 (22) International Filing Date: 18 February 2000 (18.02.00) (30) Priority Data: 2,262,214 18 February 1999 (18.02.99) CA (71)(72) Applicant and Inventor: ARBESMAN, Ray [CA/CA]; 42 Burton Road, Toronto, Ontario M5P 1V2 (CA). (74) Agent: DEETH WILLIAMS WALL LLP; National Bank Building, Suite 400, 150 York Street, Toronto, Ontario M5H 3S5 (CA).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>

(54) Title: BRAKE PLATE AND METHOD AND APPARATUS FOR MANUFACTURING SAME

**(57) Abstract**

The invention is a plate (1) for holding a friction material in a brake assembly. The plate preferably comprises a contact surface (2) for attaching the friction material to the plate, a second surface (36) opposing the contact surface (2); and a plurality of retaining structures (3) formed on the contact surface (2), each retaining structure (3) comprising a projecting member (4) extending from a point between the contact surface (2) and the second surface (36), so that the member (4) extends outwardly from the contact surface (2) for engagement with the friction material.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

BRAKE PLATE AND METHOD AND APPARATUS FOR MANUFACTURING SAME**TECHNICAL FIELD**

This invention relates to brakes, and in particular to an improved brake plate,
5 as well as a method and apparatus for manufacturing the plate.

BACKGROUND ART

The number of motor vehicles has increased greatly in recent years. There is
an interest in methods of reducing the cost of manufacturing brakes and replacement parts
on the part of both motor vehicle manufacturers and suppliers of parts for brakes. This
10 increased use has also led to a significant increase in the after-market for brake
replacement and repair. Brakes are also in increasing demand for motor vehicles such as
airplanes, trains, bicycles, all terrain vehicles and motorcycles.

Brakes, as currently manufactured, combine two main parts, namely a plate
(often called a backing plate) and a friction pad. The plate is mounted in a brake assembly,
15 and may be formed by making a plate with a variety of bosses, holes, or other features for
receiving and retaining the friction pad. The need to use high speed low cost manufacturing
methods often results in irregularities in the plate which may lead to difficulties in attaching
and/or retaining the friction pad on the plate during braking, when the friction pad is in
contact with the rapidly turning brake rotor, or even during the pre-installation handling of the
20 brake pad assembly.

There are a variety of known ways of attaching a friction pad to a plate. One
such way is to attach the friction pad to the backing plates using rivets. One disadvantage
of the riveting process is that it creates a rigid bond between the plate and the friction pad,
which can, as a result of a sudden impact, lead to breaking of the friction pad. Furthermore,
25 this process often requires one or more additional manufacturing steps with a consequent

increase in cost. In addition, when the friction pad is worn down over time, the rivets become exposed and rub against the brake rotor, causing scoring on the rotor which is costly to repair.

Another, more recently developed method of mounting the friction pad on the plate is to use a pressurised molding process to mold the friction pad directly onto the plate. In this process, the friction pad may be prepared by blending the components of the friction pad into a pre-form or cake. A conventional pressurized molding system is used to mold the friction pad pre-form onto the plate. A layer of cement or glue is often applied to the contact surface of the plate to improve the adhesion between the plate and the friction pad.

As pressure is applied to the mold assembly, the pre-form becomes heated and begins to flow, filling the mold and covering the appropriate surface of the plate. In this process, the pre-form material is intended to flow into and around the various features to improve the bond between the plate and the friction pad.

The plate is subjected to a number of forces, such as the jarring of the moving vehicle, as well as vibration caused by the rotor and noise. The problem with the prior art processes and plates is that features, such as holes and bosses, stamped into the plate often provided insufficient shear and/or tensile strength in the bond between the friction pad and plate. When additional features are stamped into the plate to increase bond strength, additional manufacturing steps are required, adding to the cost.

The most common prior art features stamped into plates are circular holes. These holes often provide unsatisfactory results because, during the molding process, the pre-form cake does not completely fill all of the holes, which in turn, leads to deficient bonding between the plate and the pre-form. The incomplete hole fills can be clearly visible, and often raise quality concerns when inspected by buyers. The incomplete hole fills also have an aesthetically displeasing appearance, which can also make them less

attractive to customers. Accordingly, it has become common practice in prior art plates to fill the incomplete hole fills with putty and to paint over them, to both hide the unsatisfactory molding results and to improve appearance. These additional manufacturing steps have the added disadvantage of increasing the cost of manufacturing the disc brake.

5 Furthermore, the holes stamped by prior art processes reduce structural strength of the plate, and make it more vulnerable to the various forces acting on it. These forces may distort the shape of the plate, leading to uneven wear on the friction pad, or can lead to structural failure of the plate.

 Another problem with brake plates is caused by the heat generated by
10 friction. The expansion and contraction values of the plate are different from those of the friction material. Braking generates heat so the plate and material are exposed to frequent heating and cooling. Since the expansion and contraction values differ, there may be a separation between the plate and the material, particularly where the plate is flat or has large flat areas. Rust can then form between the plate, which leads to noise and brake
15 failure.

 Accordingly, there is a need for a brake plate and a method of manufacturing same which can provide improved bonding with the friction pad without increasing the cost of producing the plate

20 SUMMARY OF THE INVENTION

 It is an object of the invention to provide a plate which provides an improved bond between it and the friction pad, as well as increasing the structural strength of the plate, without increasing the cost of producing the plate. In addition, it is an object of the invention to provide a method and apparatus for manufacturing the plate which reduces time
25 and cost by requiring fewer manufacturing steps, while at the same time retaining the structural strength of the backing plate.

 Further features of the invention will be described or will become apparent in

the course of the following detailed description.

The invention includes a plate for holding a friction material in a brake assembly, the plate comprising:

- a contact surface for attaching the friction material to the plate,
- 5 a second surface opposing the contact surface;
- a plurality of retaining structures formed on the contact surface, each retaining structure comprising a projecting member extending from a point between the contact surface and the second surface, so that the member extends outwardly from the contact surface for engagement with the friction material. The retaining structure may further comprise a depression surface abutting the projecting member, the depression surface extending into the contact surface. The contact surface may be curved or substantially flat. The brake 10 may comprise a disk brake or a drum brake. The plate may comprise integral retaining structures. The retaining structures can be formed from the plate, and preferably cut or scored. In a variation, the projecting member may be a burr. The burr optionally comprises a hook shape, wherein a distal end of the hook points away from the depression adjacent to the hook. The retaining structures are optionally disposed in a plurality of rows. The rows 15 are optionally substantially parallel. The rows may be usefully disposed longitudinally.

The invention also includes a method of manufacturing a brake plate for securing a friction material to a contact surface thereof, the method comprising providing:

- 20 a contact surface for attaching the friction pad to the plate,
- a second surface opposing the contact surface;
- a plurality of retaining structures formed on the contact surface, each retaining structure comprising a projecting member extending from a point between the contact surface and the second surface, so that the member extends outwardly from the contact surface for engagement with the friction pad. 25

The invention includes a brake plate, preferably a drum brake plate or a disc brake plate made according to a method of the invention or with the apparatus of the invention.

- 30 In one method, the retaining structures are formed by cutting the contact surface. The retaining structures are alternatively formed by scoring the contact surface. In another variation, the retaining structures are formed by cutting a plurality of rows of

retaining structures on the contact surface. The rows are optionally substantially parallel and/or disposed longitudinally.

5 In one embodiment, the cutting is done by a plurality of knives, each knife having a cutting edge; the edge having a plurality of teeth connected thereto. Each retaining structure is preferably made by one tooth. Each tooth preferably cuts a projecting member from the contact surface to form an adjacent depression. The knives are preferably disposed longitudinally in relation to the plate. The knives may be substantially parallel. Adjacent knives preferably move in opposing directions. The plurality of knives are preferably moving parallel to the contact surface prior to impacting the plate. The plurality of knives preferably commence to move parallel to the contact surface upon impact with the plate. The plate may be stationary while it is punched by the knives. The knives are optionally fixed in the direction perpendicular to the contact surface and the plate is impacted onto the knives.

15 Another variation of the invention relates to an apparatus for manufacturing a brake plate having a plurality of retaining structures formed on a contact surface thereof for retaining a friction material, comprising:

a means for cutting a plurality of retaining structures on the contact surface, each retaining structure comprising a projecting member extending from a point between the contact surface and the second surface, so that the member extends outwardly from the contact surface for engagement with the friction pad, the cutting means being adapted to move generally parallel to the contact surface to cut the retaining structures;

a driving means for impacting the cutting means and the contact surface of the plate to form the retaining structures.

25 The cutting means preferably comprises a plurality of knives, each knife having a cutting edge, the edge having a plurality of teeth connected thereto, each tooth adapted to form one of the plurality of retaining structures upon impact with the contact surface.

The apparatus optionally further comprises:

30 at least one drive member slidably connected to at least one side of each of the plurality of knives;

at least one slide member slidably connected to the drive member;

During impact between the knives and the contact surface, the slide member is preferably adapted to move away from the contact surface, the slide member being adapted to move the drive member generally parallel to the contact surface, the drive member being adapted to move the knives generally parallel to the contact surface.

5 The slide member may have an inclined sliding surface, the sliding surface being adapted to move the drive member generally parallel to the contact surface upon movement of the slide member. The at least one slide member can be two slide members, the at least one drive member can comprise first and second drive members, and the at least one side of the each of the knives can comprise a first side and a second side, wherein
10 first drive member is proximate to the first side of at least one knife, and the second drive member is proximate the second side of the remaining knives. The first and second sides of alternate knives are preferably proximate to the first and second drive members, respectively. The adjacent knives preferably move in opposing directions upon impact with the contact surface. The apparatus may further comprise a return means for returning the
15 knives to a starting position. The return means is optionally at least one spring attached to a first and second slide rod, the slide rods being located within a first and second guide slots defined proximate to the first and second side of each knife. The plurality of knives are preferably disposed longitudinally in relation to the plate. The apparatus knives are preferably substantially parallel to each other.

20 The slide member and the plurality of knives are preferably adapted to move generally parallel to the contact surface prior to impact with the plate. The plurality of knives are preferably adapted to move parallel to the contact surface upon impact with the plate. The plate is optionally stationary while punched by the knives. The knives are optionally fixed in the direction perpendicular to the contact surface, and the plate is driven onto the
25 knives. The impacting means optionally comprises a press having a top movable portion and a bottom stationary portion.

 The apparatus of optionally further comprises:

- a base plate secured to the top portion of the press;
- two side plates secured to the base plate, the side plates projecting
30 downwardly therefrom;
- a positioning means for maintaining the knives in proximate to each other; the

positioning means being connected to the side plates;

a force adjustment means for adjusting the force of impact of the knives against the contact surface, the force adjustment means having a pressure plate generally parallel to the base plate and at least one spring disposed between the base plate and the pressure plate, the pressure plate being connected to the knives;

wherein the first and second slide rods are suspended from the base plate.

The first and second sliding members preferably impact the bottom portion of the press prior to the knives impacting the contact surface, thereby causing the knives to move generally parallel to the contact surface prior to impact of the knives against the contact surface. The first and second sliding members preferably impact the bottom portion of the press substantially simultaneously with the knives impacting the contact surface, thereby causing the knives to move generally parallel to the contact surface substantially simultaneously with impact of the knives against the contact surface.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the invention may be more clearly understood, preferred embodiments thereof will now be described in detail by way of example, with reference to the accompanying drawings, in which:

Fig. 1 is a perspective view of a preferred embodiment of a plate according to the present invention;

Fig. 2 is a perspective view of a preferred embodiment of an apparatus for manufacturing the plate according to the present invention;

Fig. 3A is a plan view of the apparatus;

Fig. 3B is a magnified view showing the knives and teeth of the apparatus shown in Fig. 3A;

Fig. 4 is an elevation view of the apparatus with the side plates removed;

Fig. 5A is a cross-sectional view showing the apparatus impacting the bottom of a conventional press;

Fig. 5B is a cross-sectional view showing the knives beginning to cut into a blank;

Fig. 5C is a cross-sectional view showing the knives completing the cut into a blank;

5 Fig. 5D is a cross sectional view showing the apparatus impacting a press. The spring is beneath the press. A spring or a nitro spring may be used.

Fig. 6 is a perspective view of an alternate preferred embodiment of a plate according to the present invention;

Fig. 7 is a perspective view of a preferred embodiment of a knife with rows of offset teeth for manufacturing the backing plate according to the present invention. The figure shows an insert allowing one or more teeth to be releasably inserted into the knife.

Fig. 8A is a top plan view of a knife;

Fig. 8B is a side plan view of a knife;

Fig. 8C is a top plan view of a knife;

15 Fig. 8D is a side plan view of a knife;

Figs. 9A and B are perspective views of a releasable knife insert having offset teeth;

Figs. 9C is a perspective view of a releasable knife insert.

DETAILED DESCRIPTION OF THE INVENTION

20 The invention is a plate for holding a friction material in a brake assembly. The plate preferably comprises:

- (a) a contact surface for attaching the friction material to the plate,
- (b) a second surface opposing the contact surface;
- 25 (c) a plurality of retaining structures formed on the contact surface, each retaining structure comprising a projecting member extending from a point between the contact surface and the second surface, so that the member

extends outwardly from the contact surface for engagement with the friction material.

The retaining structure may further comprise a depression surface abutting the projecting member, the depression surface extending into the contact surface.

5 The brake plate, as well as the process and apparatus for manufacturing same according to the present invention are useful in the field of manufacturing of vehicle brake parts. The plate is useful in brakes for any motor vehicle, such as cars, trucks, airplanes, trains, bicycles, all terrain vehicles or motorcycles.

10 Fig. 1 shows a brake plate 1 according to a preferred embodiment of the present invention. The plate 1 has a conventional shape and any suitable thickness ($\frac{1}{8}$ - $\frac{1}{2}$ of an inch), and is preferably manufactured from metal or a metal composite adapted to withstand the rigors of a conventional braking system. The circular holes shown on the plate are not necessary and are included for illustrative purposes only. The backing plate has a contact surface 2 for molding a friction material (not shown) thereto by a conventional
15 molding process.

Any suitable number of retaining structures 3 are connected to the first surface of the backing plate. Preferably, the retaining structures are integrally formed by punching the backing plate, as described in more detail below. Each retaining structure includes a burr 4 projecting out of the first surface, which is located adjacent to a
20 corresponding depression 5 defined in the contact surface 2. Preferably, each burr is integrally formed by cutting the burr out of the first surface of the backing plate, which creates the corresponding depression 5. The projecting member extends from a point between the contact surface and the second surface 36 (in figure 6, the second surface is opposite the contact surface and appears as the flat bottom surface of the plate), so that the
25 member extends outwardly from the contact surface for engagement with the friction material. Each burr preferably has a curved shape, which curves away from its

corresponding depression.

The retaining structures 3 are preferably arranged in longitudinally disposed substantially parallel rows 6. Preferably, the position of the burr 4 and depression 5 is identical for each row, but alternates with adjacent rows, as shown in Fig. 1. Preferably, the number of rows is sufficient to cover substantially the entire surface area of the backing plate 1 in order to provide maximum bond strength. The depth of the depressions and the height of the burrs depends on the bond strength required for a particular application. Figure 6 shows a variation of the plate in which there is increased space between the structures of each row. The retaining structures in each row are spaced apart farther than those in figure 1.

The plate 1 according to the present invention does not need to be coated with an any adhesive to achieve the required bond strength with the friction material. Since the plate has a large number of projecting members, there will be no separation between the plate and the material as the plate and material are subjected to frequent heating and cooling. The plate lasts longer and is safer.

For a disc brake as shown in Figure 1, the height of the members may preferably be about 0.030 inches to 0.075 inches above the contact surface. There are preferably at least about 20 projecting members per square inch. The horizontal pitch (distance between each member) between members in the direction of chip formation may preferably range between 0.120 and 0.250 inches. The pitch between rows is preferably about 0.100 to 0.200 inches. The coverage of members on the contact surface is preferably at least about 65% for a disc brake.

For a disc brake as shown in Figure 6, the height of the members may preferably be about 0.030 inches to 0.075 inches and more preferably about 0.045 to 0.060

inches above the contact surface. There are preferably at least about 30 projecting members per square inch. The horizontal pitch (distance between each) between members in the direction of chip formation may preferably range between 0.120 and 0.250 inches and is more preferably 0.060 inches. The coverage of members on the contact surface is
5 preferably at least about 65% for a disc brake.

The method of manufacturing the backing plate 1 according to the present invention comprises placing the backing plate on a flat surface under a conventional press and punching the contact surface 2 of the backing plate with a series of substantially parallel knives 10. Referring to Fig. 2, the knives are preferably disposed substantially parallel to
10 the longitudinal axis of the backing plate. Each knife has a plurality of preferably identical teeth 11 defined along a cutting edge thereof. Each tooth forms the depression 5 and burr 4 of one retaining structure 3. The configuration of the teeth may alternate from row to row, such that every other row has an identical configuration. In Fig. 6, a knife with offset teeth is preferably used to create a checkerboard pattern (alternating retaining structure pattern)
15 between rows cut by the same knife.

Fig. 2 shows the apparatus 12 for manufacturing the backing plate according to the present invention. The apparatus is mounted to a conventional press in any suitable manner for punching the backing plate 1, as described above.

Referring to Figs. 2-4, the apparatus 12 includes a base plate 13 from which
20 two side plates 14 are suspended by preferably four conventional screws 15. Preferably, two transverse slide rods 16 are suspended from four support springs (not shown) which are each attached to one of the screws at one end and to an end of the slide rod at the other end. The slide rods are slidably secured to the knives 10 by preferably locating in guide slots 17 defined in the knives. A biasing means, such as, for example, two return springs 18
25 are connected to each slide rod to bias the slide rods toward each other. A pressure plate

19 is disposed above the non-cutting edges of the knives. Preferably, a plurality of adjustment springs 20 are disposed between the base plate and the pressure plate to urge the two apart. Two block housings 21 are mounted transversely onto the base plate adjacent to the edges of the knives. A drive block 22 is mounted on each block housing by a slide bolt 23 which is disposed substantially parallel to the longitudinal axis of the knives. A slide block 24 is slidably mounted in each housing adjacent to the drive block.

Fig. 5A shows the initial step of operation of the apparatus 12. A conventional press (not shown) drives the apparatus 12 onto a plate blank 25, such that the slide block 24 preferably impacts the bottom surface of the press 26 before the knives 10 impact the blank. The impact against the bottom surface of the plate drives the slide block up relative to the drive block 22, causing the slide block sliding surface 27 to exert a force on the drive block substantially parallel to the longitudinal axis of the knives. This force causes each drive block to move alternate knives along their longitudinal axis. Because only alternate knives contact each drive block before impact, adjacent knives are pushed in opposite directions by each drive block. Preferably, the knives are moving before the blank contacts the knives.

The teeth of the knives may be arranged along the longitudinal axis of the knife, so that they form a single row. There may be portions where no teeth are present, as in Fig. 8D. Each tooth has a leading surface which is transverse to the axis of the knife. The leading surface may be angled to determine the burr shape, in the same manner as a plow is angled. All the teeth may have a similar leading angle or they may be varied.

In a knife variation, the teeth are offset, preferably so that the teeth are arranged in two or more rows, as shown in Fig. 9. Each knife thus cuts rows of teeth along two longitudinal axes (forming two rows that are preferably substantially parallel) to provide a brake pad as shown in Fig. 6.

Referring to Figs. 5B and 5C, the impact of the knives 10 against the blank 25 may be regulated by the biasing means, preferably adjustment springs 20 (shown in Fig. 2). The adjustment springs allow the apparatus 12 to be mounted on presses having different force specifications. The adjustment springs effectively ensure that a constant
5 force is exerted against the knives, regardless of the force applied by the press. In a variation, the springs are located beneath the plate as shown in Fig. 5D. As the knives are pushed down into the blank, they also slide along the slide rods 16 parallel to their longitudinal axis, such that adjacent knives are moving in opposite directions as they cut. These simultaneous downward and sliding movements cause each tooth 11 of a knife to
10 form one retaining structure 3.

The apparatus is able to complete an entire plate in one punch. After the press lifts the apparatus 12, the slide block 24 is returned into its starting position by gravity, and the knives 10 and drive block 22 are returned to their starting positions by the slide springs 19. One skilled in the art could readily use the knives to prepare drum brake plates.

15 During the process of molding and securing the friction material to the plate, the pre-form material is set into a mold and pressed against the plate. The material flows into and surrounds each retaining structure 3 to bond with the plate 1. The retaining structures provide improved tensile strength, as well as providing improved shear resistance. The tensile and shear strengths can be varied by changing either the depth of
20 the cut (i.e. the depression 5), which also increases the height of the burr 4. These results are accomplished using a two step process, and without the need for additional features, such as holes, leading to a decreased manufacturing time and significant cost savings.

Figure 5D shows a variation of the apparatus in which a spring is mounted on a fixed press bed so that the spring is beneath the press. The spring may be a conventional
25 coil spring or a nitrogen spring. Any other suitable biasing means may be used. A knife of

the invention is shown in Figs. 7 and 8. In these figures, the teeth of each knife are aligned along an axis defined by the knife. However, the teeth may be offset to provide a brake pad of the type shown in Fig. 6. Figure 7 shows a knife with offset teeth.

Figure 7 also shows that the knife may be made with releasable inserts.

5 Broken or dull teeth may be readily changed without discarding the knife. A blank insert with no teeth may also be used. Inserts may optionally be permanently fixed in the knife. Figures 8A and 8B show the knife with continuous teeth. Figs. 8C and 8D show the knife having a blank surface where no teeth are present. The plate will have no retaining surfaces formed where the knife is blank. Figs. 9A and 9B show offset teeth. Fig. 9C

10 shows that the offset teeth are preferably about the same height above the knife.

It will be appreciated that the above description relates to the preferred embodiment by way of example only. Many variations on the invention will be obvious to those knowledgeable in the field, and such obvious variations are within the scope of the invention as described and claimed, whether or not expressly described.

CLAIMS:

1. A plate for holding a friction material in a brake assembly, the plate comprising:
a contact surface for attaching the friction material to the plate,
a second surface opposing the contact surface;
5. a plurality of retaining structures formed on the contact surface, each retaining structure comprising a projecting member extending from a point between the contact surface and the second surface, so that the member extends outwardly from the contact surface for engagement with the friction material.
10. 2. The plate of claim 1, wherein the retaining structure further comprises a depression surface abutting the projecting member, the depression surface extending into the contact surface.
3. The plate of claim 1 or 2, wherein the contact surface is curved or substantially flat.
4. The plate of any one of claims 1-3, wherein the brake comprises a disk brake or a drum brake.
15. 5. The plate of any one of claims 1-4, wherein the plate comprises integral retaining structures.
6. The plate of any one of claims 1-5, wherein the retaining structures are formed from the plate.
20. 7. The plate of any one of claims 1-6, wherein the retaining structures are cut from the plate.
8. The plate of any one of claims 1-7, wherein the retaining structures are scored from the plate.
9. The plate of any one of claims 1-8, wherein the projecting member comprises a burr.
25. 10. The plate of any one of claims 2-9, wherein the burr comprises a hook shape, wherein a distal end of the hook points away from the depression adjacent to the hook.
11. The plate of any one of claims 1-10, wherein the retaining structures are disposed in a plurality of rows.
12. The plate of claim 11, wherein the rows are substantially parallel.

13. The plate of claim 11 or 12, wherein the rows are disposed longitudinally.
14. A method of manufacturing a brake plate for securing a friction material to a contact surface thereof, the method comprising providing:
- 5 a contact surface for attaching the friction pad to the plate,
- a second surface opposing the contact surface;
- a plurality of retaining structures formed on the contact surface, each retaining structure comprising a projecting member extending from a point between the contact surface and the second surface, so that the member extends outwardly from the contact surface for engagement with the friction pad.
- 10 15. The method of claim 14, wherein the retaining structures are formed by cutting the contact surface.
16. The method of claim 14, wherein the retaining structures are formed by scouring the contact surface.
17. The method of claim 14, wherein the retaining structures are formed by cutting a
- 15 plurality of rows of retaining structures on the contact surface.
18. The method of claim 17, wherein the rows are substantially parallel.
19. The method of claim 17, wherein the rows are disposed longitudinally.
20. The method of any one of claims 14-19, wherein the cutting is done by a plurality of knives, each knife having a cutting edge, the edge having a plurality of teeth connected
- 20 thereto.
21. The method of claim 120, wherein each retaining structure is made by one tooth.
22. The method of claim 21, wherein each tooth cuts a projecting member from the contact surface to form an adjacent depression.
23. The method of claim 22, wherein the knives are disposed longitudinally in relation to
- 25 the plate.
24. The method of claim 23, wherein the knives are substantially parallel.
25. The method of claim 24, wherein adjacent knives move in opposing directions.
26. The method of claim 25, wherein the plurality of knives are moving parallel to the

contact surface prior to impacting the plate.

27. The method of claim 26, wherein the plurality of knives commence to move parallel to the contact surface upon impact with the plate.

28. An apparatus for manufacturing a brake plate having a plurality of retaining structures formed on a contact surface thereof for retaining a friction material, comprising:

5 a means for cutting a plurality of retaining structures on the contact surface, each retaining structure comprising a projecting member extending from a point between the contact surface and the second surface, so that the member extends outwardly from the contact surface for engagement with the friction pad, the cutting means being adapted to
10 move generally parallel to the contact surface to cut the retaining structures;

a driving means for impacting the cutting means and the contact surface of the plate to form the retaining structures.

29. The apparatus of claim 28, wherein the cutting means comprises a plurality of knives, each knife having a cutting edge, the edge having a plurality of teeth connected
15 thereto, each tooth adapted to form one of the plurality of retaining structures upon impact with the contact surface.

30. The apparatus of claim 28, wherein the apparatus further comprises:

at least one drive member slidably connected to at least one side of each of the plurality of knives;

20 at least one slide member slidably connected to the drive member;

wherein during impact between the knives and the contact surface, the slide member is adapted to move away from the contact surface, the slide member being adapted to move the drive member generally parallel to the contact surface, the drive member being adapted to move the knives generally parallel to the contact surface.

25 31. The apparatus of claim 28, wherein the slide member has an inclined sliding surface, the sliding surface being adapted to move the drive member generally parallel to the contact surface upon movement of the slide member.

32. The apparatus of claim 29, wherein the at least one slide member is two slide members, the at least one drive member comprises a first and second drive members, and
30 the at least one side of the each of the knives comprises a first side and a second side,

wherein first drive member is proximate to the first side of at least one knife, and the second drive member is proximate the second side of the remaining knives.

33. The apparatus of claim 32, wherein the first and second sides of alternate knives are proximate to the first and second drive members, respectively.

5 34. The apparatus of claim 32, wherein adjacent knives move in opposing directions upon impact with the contact surface.

35. The apparatus of claim 33 further comprising a return means for returning the knives to a starting position.

10 36. The apparatus of claim 34, wherein the return means is at least one spring attached to a first and second slide rod, the slide rods being located within a first and second guide slots defined proximate to the first and second side of each knife.

37. The apparatus of claim 30, wherein the plurality of knives are disposed longitudinally in relation to the plate.

15 38. The apparatus of claim 37, wherein the knives are substantially parallel to each other.

39. The apparatus of claim 32, wherein the slide member the plurality of knives are adapted to move generally parallel to the contact surface prior to impact with the plate.

40. The apparatus of claim 32, wherein the plurality of knives are adapted to move parallel to the contact surface upon impact with the plate.

20 41. The apparatus of claim 33, wherein the plate is stationary and the plate is punched by the knives.

42. The apparatus of claim 29, wherein the knives are fixed in the direction perpendicular to the contact surface, and the plate is driven onto the knives.

25 43. The apparatus of claim 28, wherein the impacting means comprises a press having a top movable portion and a bottom stationary portion.

44. The apparatus of claim 28, wherein the apparatus further comprises:

a base plate secured to the top portion of the press;

two side plates secured to the base plate, the side plates projecting downwardly therefrom;

a positioning means for maintaining the knives in proximate to each other, the positioning means being connected to the side plates;

5 a force adjustment means for adjusting the force of impact of the knives against the contact surface, the force adjustment means having a pressure plate generally parallel to the base plate and at least one spring disposed between the base plate and the pressure plate, the pressure plate being connected to the knives;

wherein the first and second slide rods are suspended from the base plate.

45. The apparatus of claim 44, wherein the first and second sliding members impact the bottom portion of the press prior to the knives impacting the contact surface, thereby
10 causing the knives to move generally parallel to the contact surface prior to impact of the knives against the contact surface.

46. The apparatus of claim 45, wherein the first and second sliding members impact the bottom portion of the press substantially simultaneously with the knives impacting the contact surface, thereby causing the knives to move generally parallel to the contact
15 surface substantially simultaneously with impact of the knives against the contact surface.




FIG.1




FIG.2

3/12




FIG. 3A




FIG. 3B




FIG. 4

5/12




FIG. 5A






FIG. 5B

6/12







FIG. 6



9/12




FIG. 8A




FIG. 8B



FIG. 8C




FIG. 8D

11/12




FIG. 9A

← 30




FIG. 9B




FIG.9C

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 00/00159

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F16D69/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F16D B210

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 799 579 A (MYERS PAUL A ET AL) 24 January 1989 (1989-01-24) column 4, line 33 - line 48; figures 5,6	1-24
X	GB 2 245 667 A (FERODO LTD) 8 January 1992 (1992-01-08) page 2, line 23 -page 3, line 23 figures 2-4	1-14
A	US 4 569 424 A (TAYLOR JR JAMES L) 11 February 1986 (1986-02-11) abstract; figures 1,2	1, 14, 30
A	GB 2 299 382 A (T & N TECHNOLOGY LTD) 2 October 1996 (1996-10-02) abstract; figure 1	1
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

28 June 2000

Date of mailing of the international search report

04/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Topolski, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 00/00159

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 3 557 407 A (LEMELSON JEROME H) 26 January 1971 (1971-01-26) column 2, line 25 - line 28 column 7, line 64 -column 8, line 44 figure 8</p> <p>-----</p>	30

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 00/00159

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4799579	A	24-01-1989	NONE	
GB 2245667	A	08-01-1992	NONE	
US 4569424	A	11-02-1986	NONE	
GB 2299382	A	02-10-1996	WO 9630668 A	03-10-1996
US 3557407	A	26-01-1971	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)